LG Display

LP156WF4
Liquid Crystal Display

Product Specification

SPECIFICATION
FOR
APPROVAL

(   ) **Preliminary Specification**
(◆) **Final Specification**

Title	15.6" Full HD TFT LCD

Customer	ASUS
MODEL	

SUPPLIER	LG Display Co., Ltd.
*MODEL	LP156WF4
Suffix	SPB1

*When you obtain standard approval,
please use the above model name without suffix

APPROVED BY	SIGNATURE
/	
/	
/	

APPROVED BY	SIGNATURE
J. Y. Lee / S.Manager	
REVIEWED BY	
C. I. Kim / Manager	
PREPARED BY	
S. B. Park / Engineer	
S. I. Joo / Engineer	

Please return 1 copy for your confirmation with
your signature and comments.

Products Engineering Dept.
LG Display Co., Ltd

Contents

Product Specification

RECORD OF REVISIONS

Revision No	Revision Date	Page	Description	EDID ver
1.0	Jul. 27. 2012	-	Final Specification	1.0

LG Display

Product Specification

1. General Description

 The LP156WF4 is a Color Active Matrix Liquid Crystal Display with an integral LED backlight system. The matrix employs a-Si Thin Film Transistor as the active element. It is a transmissive type display operating in the normally black mode. This TFT-LCD has 15.6 inches diagonally measured active display area with FHD resolution (1920 horizontal by 1080 vertical pixel array). Each pixel is divided into Red, Green and Blue sub-pixels or dots which are arranged in vertical stripes. Gray scale or the brightness of the sub-pixel color is determined with a 6-bit gray scale signal for each dot, thus, presenting a palette of more than 262,144 colors. The LP156WF4 has been designed to apply the interface method that enables low power, high speed, low EMI. The LP156WF4 is intended to support applications where thin thickness, low power are critical factors and graphic displays are important. In combination with the vertical arrangement of the sub-pixels, the LP156WF4 characteristics provide an excellent flat display for office automation products such as Notebook PC.

General Features

Active Screen Size	15.6 inches diagonal
Outline Dimension	359.5(H, typ.) × 224.1(V, typ.) × 3.4(D,max) [mm] (with Bracket & PCB Board)
Pixel Pitch	0.17925 mm x 0.17925 mm
Pixel Format	1920 horiz. By 1080 vert. Pixels RGB strip arrangement
Color Depth	6-bit, 262,144 colors
Luminance, White	300 cd/m² (Typ.5 point)
Power Consumption	Total 7.28 W (Typ.) Logic : 1.68 W (Typ.@ Mosaic), B/L : 5.6 W (Typ.@VLED12V)
Weight	330g (Max.) / 320g (Typ.)
Display Operating Mode	Normally Black
Surface Treatment	Anti glare treatment of the front Polarizer
RoHS Compliance	Yes
BFR / PVC / As Free	Yes for all

LG Display

Product Specification

2. Absolute Maximum Ratings

The following are maximum values which, if exceeded, may cause faulty operation or damage to the unit.

Table 1. ABSOLUTE MAXIMUM RATINGS

Parameter	Symbol	Values		Units	Notes
		Min	Max		
Power Input Voltage	VCC	-0.3	4.0	Vdc	at 25 ± 5°C
Operating Temperature	TOP	0	50	°C	1
Storage Temperature	HST	-20	60	°C	1
Operating Ambient Humidity	HOP	10	90	%RH	1
Storage Humidity	HST	10	90	%RH	1

Note : 1. Temperature and relative humidity range are shown in the figure below.
        Wet bulb temperature should be 39°C Max, and no condensation of water.
Note : 2. Storage Condition is guaranteed under packing condition.

Product Specification

3. Electrical Specifications

3-1. Electrical Characteristics

The LP156WF4 requires two power inputs. The first logic is employed to power the LCD electronics and to drive the TFT array and liquid crystal. The second backlight is the input about LED BL with LED Driver.

Table 2. ELECTRICAL CHARACTERISTICS

Parameter		Symbol	Values			Unit	Notes
			Min	Typ	Max		
LOGIC :							
Power Supply Input Voltage		V_{CC}	3.0	3.3	3.6	V	1
Power Supply Input Current	Mosaic	I_{CC}	-	510	585	mA	2
Power Consumption		P_{CC}	-	1.68	1.93	W	2
Power Supply Inrush Current		I_{CC_P}	-	-	1500	mA	3
Differential Impedance		Z_m	90	100	110	Ω	4
BACKLIGHT : (with LED Driver)							
LED Power Input Voltage		V_{LED}	7.0	12.0	21.0	V	5
LED Power Input Current		I_{LED}	-	470	520	mA	6
LED Power Consumption		P_{LED}	-	5.6	6.2	W	6
LED Power Inrush Current		I_{LED_P}	-	-	1500	mA	7
PWM Duty Ratio			5	-	100	%	8
PWM Jitter		-	0	-	0.2	%	9
PWM Impedance		Z_{PWM}	20	40	60	kΩ	
PWM Frequency		F_{PWM}	200	-	1000	Hz	10
PWM High Level Voltage		V_{PWM_H}	3.0	-	5.3	V	
PWM Low Level Voltage		V_{PWM_L}	0	-	0.3	V	
LED_EN Impedance		Z_{PWM}	20	40	60	kΩ	
LED_EN High Voltage		$V_{LED\_EN\_H}$	3.0	-	5.3	V	
LED_EN Low Voltage		$V_{LED\_EN\_L}$	0	-	0.3	V	
Life Time			12,000	-	-	Hrs	11

LP156WF4
Liquid Crystal Display

LG Display

### Product Specification

Note)

1. The measuring position is the connector of LCM and the test conditions are under 25℃, fv = 60Hz, Black pattern.

2. The specified Icc current and power consumption are under the Vcc = 3.3V , 25℃, fv = 60Hz condition and Mosaic pattern.

2. This Spec. is the max load condition for the cable impedance designing.

3. The below figures are the measuring Vcc condition and the Vcc control block LGD used.
   The Vcc condition is same as the minimum of T1 at Power on sequence.

4. This impedance value is needed for proper display and measured form eDP Tx to the mating connector.

5. The measuring position is the connector of LCM and the test conditions are under 25℃.

6. The current and power consumption with LED Driver are under the Vled = 12.0V , 25℃, Dimming of Max luminance and White pattern with the normal frame frequency operated(60Hz).

7. The below figures are the measuring Vled condition and the Vled control block LGD used.
   VLED control block is same with Vcc control block.

8. The operation of LED Driver below minimum dimming ratio may cause flickering or reliability issue.

9. If Jitter of PWM is bigger than maximum, it may induce flickering.

10. This Spec. is not effective at 100% dimming ratio as an exception because it has DC level equivalent to 0Hz. In spite of acceptable range as defined, the PWM Frequency should be fixed and stable for more consistent brightness control at any specific level desired.

11. The life time is determined as the time at which brightness of LCD is 50% compare to that of minimum value specified in table 7. under general user condition.

LP156WF4
Liquid Crystal Display

Product Specification

3-2. Interface Connections

This LCD employs two interface connections, a 30 pin connector used for the module electronics interface and the other connector used for the integral backlight system.

### Table 3. MODULE CONNECTOR PIN CONFIGURATION (CN1)

Pin	Symbol	Description	Notes
1	NC	NO Connect	**[Interface Chip]**
2	GND	High Speed (Main Link) Ground	1. LCD :
3	Lane1_N	Complement Signal-Lane 1	Analogix, ANX9858 (LCD Controller
4	Lane1_p	True Signal-Main Lane 1	Including eDP Receiver.
5	GND	High Speed (Main Link) Ground	2. System : TBD or equivalent
6	Lane0_N	Complement Signal-Lane 0	* Pin to Pin compatible with eDP
7	Lane0_p	True Signal-Main Lane 0	
8	GND	High Speed (Main Link) Ground	**[Connector]**
9	AUX_P	True Signal-Auxiliary Channel	CABLINE-VS RECE ASS'Y, I-PEX
10	AUX_N	Complement Signal-Auxiliary Channel	or its compatibles
11	GND	High Speed (Main Link) Ground	
12	VCC	LCD Logic and driver power (3.3V Typ.)	**[Mating Connector]**
13	VCC	LCD Logic and driver power (3.3V Typ.)	CABLINE-VS PLUG CABLE
14	NC	NO Connect	ASS'Y or equivalent.
15	GND	Ground	
16	GND	Ground	**[Connector pin arrangement]**
17	HPD	HPD signal pin	
18	GND	LED Backlight Ground	
19	GND	LED Backlight Ground	30 ▯▯▯▯▯▯▯▯▯▯▯▯▯▯▯ 1
20	GND	LED Backlight Ground	
21	GND	LED Backlight Ground	[LCD Module Rear View]
22	LED_EN	LED Backlight On/Off	
23	PWM	System PWM Signal input for dimming	
24	NC	NO Connect	
25	NC	NO Connect	
26	VLED	LED Backlight Power (7.0V-21V)	
27	VLED	LED Backlight Power (7.0V-21V)	
28	VLED	LED Backlight Power (7.0V-21V)	
29	VLED	LED Backlight Power (7.0V-21V)	
30	NC	NO Connect	

Ver. 1.0   Jul. 27, 2012   8 / 26

LG Display

Product Specification

3-3. eDP Signal Timing Specifications

3-3-1. DC Specification

The VESA Display Port related AC specification is compliant with the VESA Display Port Standard v1.1a.

Description	Symbol	Min	Max	Unit	Notes
Differential peak-to-peak Input voltage	VDIFF p-p	120	-	mV	For high bit rate
		40	-		For reduced bit rate
Rx DC common mode voltage	VCM	0	2.0	V	-

3-3-2. AC Specification

The VESA Display Port related AC specification is compliant with the VESA Display Port Standard v1.1a.

Description	Symbol	Min	Typ	Max	Unit	Notes
Unit Interval for high bit rate (2.7Gbps/lane)	UI_High_Rate	-	370	-	ps	Range is nominal ±350ppm. DisplayPort Link Rx does not require local crystal for link clock generation
Unit Interval for high bit rate (1.62Gbps/lane)	UI_Low_Rate	-	617	-	ps	
Lane-to-Lane skew	V Rx-SKEW-INTER_PAIR	-	-	5200	ps	-
Lane intra-pair skew	V Rx-SKEW-INTRA_PAIR	-	-	100	ps	For high bit rate
		-	-	300	ps	For reduced bit rate

LG Display

Product Specification

1. General Description

 The LP156WF4 is a Color Active Matrix Liquid Crystal Display with an integral LED backlight system. The matrix employs a-Si Thin Film Transistor as the active element. It is a transmissive type display operating in the normally black mode. This TFT-LCD has 15.6 inches diagonally measured active display area with FHD resolution (1920 horizontal by 1080 vertical pixel array). Each pixel is divided into Red, Green and Blue sub-pixels or dots which are arranged in vertical stripes. Gray scale or the brightness of the sub-pixel color is determined with a 6-bit gray scale signal for each dot, thus, presenting a palette of more than 262,144 colors. The LP156WF4 has been designed to apply the interface method that enables low power, high speed, low EMI. The LP156WF4 is intended to support applications where thin thickness, low power are critical factors and graphic displays are important. In combination with the vertical arrangement of the sub-pixels, the LP156WF4 characteristics provide an excellent flat display for office automation products such as Notebook PC.

General Features

Active Screen Size	15.6 inches diagonal
Outline Dimension	359.5(H, typ.) × 224.1(V, typ.) × 3.4(D,max) [mm] (with Bracket & PCB Board)
Pixel Pitch	0.17925 mm x 0.17925 mm
Pixel Format	1920 horiz. By 1080 vert. Pixels RGB strip arrangement
Color Depth	6-bit, 262,144 colors
Luminance, White	300 cd/m² (Typ.5 point)
Power Consumption	Total 7.28 W (Typ.) Logic : 1.68 W (Typ.@ Mosaic), B/L : 5.6 W (Typ.@VLED12V)
Weight	330g (Max.) / 320g (Typ.)
Display Operating Mode	Normally Black
Surface Treatment	Anti glare treatment of the front Polarizer
RoHS Compliance	Yes
BFR / PVC / As Free	Yes for all

LP156WF4
Liquid Crystal Display

Product Specification

3-6. Color Input Data Reference

The brightness of each primary color (red, green and blue) is based on the 6-bit gray scale data input for the color ; the higher the binary input, the brighter the color. The table below provides a reference for color versus data input.

Table 5. COLOR DATA REFERENCE

Color		Input Color Data																		
		RED						GREEN						BLUE						
		MSB					LSB	MSB					LSB	MSB					LSB	
		R5	R4	R3	R2	R1	R0	G5	G4	G3	G2	G1	G0	B5	B4	B3	B2	B1	B0
Basic Color	Black	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	Red	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	0	0
	Green	0	0	0	0	0	0	1	1	1	1	1	1	0	0	0	0	0	0
	Blue	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	1
	Cyan	0	0	0	0	0	0	1	1	1	1	1	1	1	1	1	1	1	1
	Magenta	1	1	1	1	1	1	0	0	0	0	0	0	1	1	1	1	1	1
	Yellow	1	1	1	1	1	1	1	1	1	1	1	1	0	0	0	0	0	0
	White	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1
RED	RED (00)	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	RED (01)	0	0	0	0	0	1	0	0	0	0	0	0	0	0	0	0	0	0
	…			…						…						…			
	RED (62)	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	0	0	0
	RED (63)	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	0	0
GREEN	GREEN (00)	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	GREEN (01)	0	0	0	0	0	0	0	0	0	0	0	1	0	0	0	0	0	0
	...			…						…						…			
	GREEN (62)	0	0	0	0	0	0	1	1	1	1	1	0	0	0	0	0	0	0
	GREEN (63)	0	0	0	0	0	0	1	1	1	1	1	1	0	0	0	0	0	0
BLUE	BLUE (00)	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	BLUE (01)	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1
	…			…						…						…			
	BLUE (62)	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	0
	BLUE (63)	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	1

LG Display

Product Specification

3-7. Power Sequence

Table 6. POWER SEQUENCE TABLE

Logic Parameter	Value			Units	LED Parameter	Value			Units
	Min.	Typ.	Max.			Min.	Typ.	Max.	
T_1	0.5	-	10	ms	T_9	200	-	-	ms
T_2	0	-	200	ms	T_{10}	0	-	-	ms
T_3	50	75	-	ms	T_{11}	0	-	-	ms
T_4	0	-	-	ms	T_{12}	0.5	-	-	ms
T_5	0	-	-	ms	T_{13}	0	-	5000	ms
T_6	500	-	-	ms	T_{14}	10	-	-	ms
T_7	3	-	10	ms	T_{15}	10	-	-	ms
T_8	200	-	-	ms					

Note)
1. Do not insert the mating cable when system turn on.
2. Valid Data have to meet "3-3. eDP Signal Timing Specifications"
3. eDP, LED_EN and PWM need to be on pull-down condition on invalid status.
4. LGD recommend the rising sequence of VLED after the Vcc and valid status of eDP turn on.

LG Display

Product Specification

4. Optical Specification

Optical characteristics are determined after the unit has been 'ON' and stable for approximately 30 minutes in a dark environment at 25°C. The values specified are at an approximate distance 50cm from the LCD surface at a viewing angle of Φ and Θ equal to 0°.
FIG. 1 presents additional information concerning the measurement equipment and method.

### FIG. 1 Optical Characteristic Measurement Equipment and Method

Table 9. OPTICAL CHARACTERISTICS

Ta=25°C, VCC=3.3V, fv=60Hz, f_{CLK}= 69.0MHz

Parameter		Symbol	Values			Units	Notes
			Min	Typ	Max		
Contrast Ratio		CR	400	700	-		1
Surface Luminance, white		L_{WH}	255	300	-	cd/m^2	2
Luminance Variation		δ_{WHITE}	-	1.4	1.6		3
Response Time		Tr_R+ Tr_D	-	35	50	ms	4
Color Coordinates							
	RED	RX	0.599	0.629	0.659		
		RY	0.320	0.350	0.380		
	GREEN	GX	0.319	0.349	0.379		
		GY	0.584	0.614	0.644		
	BLUE	BX	0.124	0.154	0.184		
		BY	0.082	0.112	0.142		
	WHITE	WX	0.283	0.313	0.343		
		WY	0.299	0.329	0.359		
Viewing Angle							5
	x axis, right(Φ=0°)	Θr	80	85	-	degree	
	x axis, left (Φ=180°)	Θl	80	85	-	degree	
	y axis, up (Φ=90°)	Θu	80	85	-	degree	
	y axis, down (Φ=270°)	Θd	80	85	-	degree	
Gray Scale							6

LG Display

Product Specification

Note)
1. Contrast Ratio(CR) is defined mathematically as

$$\text{Contrast Ratio} = \frac{\text{Surface Luminance with all white pixels}}{\text{Surface Luminance with all black pixels}}$$

2. Surface luminance is the average of 5 point across the LCD surface 50cm from the surface with all pixels displaying white. For more information see FIG 1.

$$\text{LWH} = \text{Average}(L1, L2, \ldots L5)$$

3. The variation in surface luminance , The panel total variation (δ WHITE) is determined by measuring LN at each test position 1 through 13 and then defined as following numerical formula.
   For more information see FIG 2.

$$\delta \text{ WHITE} = \text{Maximum}(L1, L2, \ldots L13) / \text{Minimum}(L1, L2, \ldots L13)$$

4. Response time is the time required for the display to transition from white to black (rise time, TrR) and from black to white(Decay Time, TrD). For additional information see FIG 3.

5. Viewing angle is the angle at which the contrast ratio is greater than 10. The angles are determined for the horizontal or x axis and the vertical or y axis with respect to the z axis which is normal to the LCD surface. For more information see FIG 4.

6. Gray scale specification   * fV = 60Hz

Gray Level	Luminance [%] (Typ)
L0	0.13
L7	0.70
L15	4.53
L23	10.8
L31	20.3
L39	33.0
L47	49.0
L55	73.0
L63	100.0

Product Specification

FIG. 2 Luminance

<Measuring point for Average Luminance & measuring point for Luminance variation>

H,V : ACTIVE AREA
A : H/4 mm
B : V/4 mm
POINTS: 13 POINTS

FIG. 3 Response Time

The response time is defined as the following figure and shall be measured by switching the input signal for "black" and "white".


FIG. 4 Viewing angle

<Dimension of viewing angle range>

$\phi = 90$, Up
$\phi = 180$, Left
$\phi = 0$, Right
$\phi = 270$, Down

LP156WF4
Liquid Crystal Display

LG Display

5. Mechanical Characteristics

The contents provide general mechanical characteristics for the model LP156WF4. In addition the figures in the next page are detailed mechanical drawing of the LCD.

Outline Dimension	Horizontal	359.5 ± 0.5mm
	Vertical	207.7 ± 0.5mm
	Thickness	3.4mm (max)
Bezel Area	Horizontal	347.55 ± 0.5mm
	Vertical	196.9 ± 0.5mm
Active Display Area	Horizontal	344.16 ± 0.3 mm
	Vertical	193.59 ± 0.3 mm
Weight	330g (Max.) / 320g (Typ.)	
Surface Treatment	Anti-Glare treatment of the front polarizer	

LG Display

Product Specification

<FRONT VIEW>

Note) Unit:[mm], General tolerance: ± 0.5mm

LG Display

LP156WF4
Liquid Crystal Display

Product Specification

<REAR VIEW>

Note) Unit:[mm], General tolerance: ± 0.5mm

LG Display

Product Specification

6. Reliability

Environment test condition

No.	Test Item	Conditions
1	High temperature storage test	Ta= 60°C, 240h
2	Low temperature storage test	Ta= -20°C, 240h
3	High temperature operation test	Ta= 50°C, 50%RH, 240h
4	Low temperature operation test	Ta= 0°C, 240h
5	Vibration test (non-operating)	Sine wave, 5 ~ 150Hz, 1.5G, 0.37oct/min 3 axis, 30min/axis
6	Shock test (non-operating)	- No functional or cosmetic defects following a shock to all 6 sides delivering at least 180 G in a half sine pulse no longer than 2 ms to the display module - No functional defects following a shock delivering at least 200 g in a half sine pulse no longer than 2 ms to each of 6 sides. Each of the 6 sides will be shock tested with one each display, for a total of 6 displays
7	Altitude operating storage / shipment	0 ~ 10,000 feet (3,048m) 24Hr 0 ~ 40,000 feet (12,192m) 24Hr

{ Result Evaluation Criteria }
 There should be no change which might affect the practical display function when the display quality
test is conducted under normal operating condition.

LG Display

Product Specification

7. International Standards

7-1. Safety

a) UL 60950-1, Second Edition, Underwriters Laboratories Inc.
   Information Technology Equipment - Safety - Part 1 : General Requirements.

b) CAN/CSA C22.2 No.60950-1-07, Second Edition, Canadian Standards Association.
   Information Technology Equipment - Safety - Part 1 : General Requirements.

c) EN 60950-1:2006 + A11:2009, European Committee for Electro technical Standardization (CENELEC).
   Information Technology Equipment - Safety - Part 1 : General Requirements.

d) IEC 60950-1:2005, Second Edition, The International Electro technical Commission (IEC).
   Information Technology Equipment - Safety - Part 1 : General Requirements.

7-2. EMC

a) ANSI C63.4 "American National Standard for Methods of Measurement of Radio-Noise
   Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz."
   American National Standards Institute (ANSI), 2003.

b) CISPR 22 "Information technology equipment – Radio disturbance characteristics – Limit and
   methods of measurement." International Special Committee on Radio Interference
   (CISPR), 2005.

c) CISPR 13 "Sound and television broadcast receivers and associated equipment – Radio disturbance
   characteristics – Limits and method of measurement." International Special Committee on Radio
   Interference (CISPR), 2006.

7-3. Environment

a) RoHS, Directive 2002/95/EC of the European Parliament and of the council of 27 January 2003

LP156WF4
Liquid Crystal Display

Product Specification

8. Packing

8-1. Designation of Lot Mark

a) Lot Mark

| A | B | C | D | E | F | G | H | I | J | K | L | M |

A,B,C : SIZE(INCH)   D : YEAR
E : MONTH   F ~ M : SERIAL NO.

Note
   1. YEAR

Year	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020
Mark	A	B	C	D	E	F	G	H	J	K

   2. MONTH

Month	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
Mark	1	2	3	4	5	6	7	8	9	A	B	C

b) Location of Lot Mark

Serial No. is printed on the label. The label is attached to the backside of the LCD module.
This is subject to change without prior notice.

8-2. Packing Form

a) Package quantity in one box : 20 pcs

b) Box Size : 478 x 365 x 328

LG Display

LP156WF4
Liquid Crystal Display

Product Specification

9. PRECAUTIONS

Please pay attention to the followings when you use this TFT LCD module.

9-1. MOUNTING PRECAUTIONS

(1) You must mount a module using holes arranged in four corners or four sides.
(2) You should consider the mounting structure so that uneven force (ex. Twisted stress) is not applied to the module. And the case on which a module is mounted should have sufficient strength so that external force is not transmitted directly to the module.
(3) Please attach the surface transparent protective plate to the surface in order to protect the polarizer. Transparent protective plate should have sufficient strength in order to the resist external force.
(4) You should adopt radiation structure to satisfy the temperature specification.
(5) Acetic acid type and chlorine type materials for the cover case are not desirable because the former generates corrosive gas of attacking the polarizer at high temperature and the latter causes circuit break by electro-chemical reaction.
(6) Do not touch, push or rub the exposed polarizers with glass, tweezers or anything harder than HB pencil lead. And please do not rub with dust clothes with chemical treatment.
   Do not touch the surface of polarizer for bare hand or greasy cloth.(Some cosmetics are detrimental to the polarizer.)
(7) When the surface becomes dusty, please wipe gently with absorbent cotton or other soft materials like chamois soaks with petroleum benzene. Normal-hexane is recommended for cleaning the adhesives used to attach front / rear polarizers. Do not use acetone, toluene and alcohol because they cause chemical damage to the polarizer.
(8) Wipe off saliva or water drops as soon as possible. Their long time contact with polarizer causes deformations and color fading.
(9) Do not open the case because inside circuits do not have sufficient strength.
(10) When handling the LCD module, it needs to handle with care not to give mechanical stress to the PCB and Mounting Hole area."

9-2. OPERATING PRECAUTIONS

(1) The spike noise causes the mis-operation of circuits. It should be lower than following voltage :
   V=± 200mV(Over and under shoot voltage)

(2) Response time depends on the temperature.(In lower temperature, it becomes longer.)
(3) Brightness depends on the temperature. (In lower temperature, it becomes lower.)
   And in lower temperature, response time(required time that brightness is stable after turned on) becomes longer.
(4) Be careful for condensation at sudden temperature change. Condensation makes damage to polarizer or electrical contacted parts. And after fading condensation, smear or spot will occur.
(5) When fixed patterns are displayed for a long time, remnant image is likely to occur.
(6) Module has high frequency circuits. Sufficient suppression to the electromagnetic interference shall be done by system manufacturers. Grounding and shielding methods may be important to minimized the interference.

| Ver. 1.0 | Jul. 27, 2012 | 22 / 26 |

LG Display

LP156WF4
Liquid Crystal Display

Product Specification

9-3. ELECTROSTATIC DISCHARGE CONTROL

Since a module is composed of electronic circuits, it is not strong to electrostatic discharge. Make certain that treatment persons are connected to ground through wrist band etc. And don't touch interface pin directly.

9-4. PRECAUTIONS FOR STRONG LIGHT EXPOSURE

Strong light exposure causes degradation of polarizer and color filter.

9-5. STORAGE

When storing modules as spares for a long time, the following precautions are necessary.

(1) Store them in a dark place. Do not expose the module to sunlight or fluorescent light. Keep the temperature between 5°C and 35°C at normal humidity.
(2) The polarizer surface should not come in contact with any other object.
It is recommended that they be stored in the container in which they were shipped.

9-6. HANDLING PRECAUTIONS FOR PROTECTION FILM

(1) When the protection film is peeled off, static electricity is generated between the film and polarizer. This should be peeled off slowly and carefully by people who are electrically grounded and with well ion-blown equipment or in such a condition, etc.
(2) The protection film is attached to the polarizer with a small amount of glue. If some stress is applied to rub the protection film against the polarizer during the time you peel off the film, the glue is apt to remain on the polarizer.
Please carefully peel off the protection film without rubbing it against the polarizer.
(3) When the module with protection film attached is stored for a long time, sometimes there remains a very small amount of glue still on the polarizer after the protection film is peeled off.
(4) You can remove the glue easily. When the glue remains on the polarizer surface or its vestige is recognized, please wipe them off with absorbent cotton waste or other soft material like chamois soaked with normal-hexane.

LG Display

LP156WF4
Liquid Crystal Display

Product Specification

APPENDIX A. Enhanced Extended Display Identification Data (EEDID™)　1/3

| | Written by | gocho@lbdisplay.com | | EDID Data_ ver. 1.0 | | 2012/7/14 |

	Byte (Dec)	Byte (Hex)	Field Name and Comments	Value (Hex)	Value (Bin)
Header	0	00	Header	00	00000000
	1	01	Header	FF	11111111
	2	02	Header	FF	11111111
	3	03	Header	FF	11111111
	4	04	Header	FF	11111111
	5	05	Header	FF	11111111
	6	06	Header	FF	11111111
	7	07	Header	00	00000000
Vendor / Product EDID Version	8	08	ID Manufacture Name LGD	30	00110000
	9	09	ID Manufacture Name	E4	11100100
	10	0A	ID Product Code 0323h	23	00100011
	11	0B	(Hex LSB first)	03	00000011
	12	0C	ID Serial No. - Optional ("00h" if not used, Number Only and LSB First)	00	00000000
	13	0D	ID Serial No. - Optional ("00h" if not used, Number Only and LSB First)	00	00000000
	14	0E	ID Serial No. - Optional ("00h" if not used, Number Only and LSB First)	00	00000000
	15	0F	ID Serial No. - Optional ("00h" if not used, Number Only and LSB First)	00	00000000
	16	10	Week of Manufacture - Optional 00 weeks	00	00000000
	17	11	Year of Manufacture 2012 years	16	00010110
	18	12	EDID structure version # = 1	01	00000001
	19	13	EDID revision # = 4	04	00000100
Display Parameters	20	14	Video input Definition = Input is a Digital Video signal interface , Color Bit Depth : 6 Bits per Primary Color , Digital Video Interface Standard Supported: DisplayPort is supported	95	10010101
	21	15	Horizontal Screen Size (Rounded cm) = 35 cm	23	00100011
	22	16	Vertical Screen Size (Rounded cm) = 19 cm	13	00010011
	23	17	Display Transfer Characteristic (Gamma)= (gamma*100)-100 = Example (2.2*100)-100=120	78	01111000
	24	18	Feature Support (Display Power Management(DPM) : Standby Mode is not supported, Suspend Mode is not supported, Active Off = Very Low Power is not supported ,Supported Color Encoding Formats : RGB 4:4:4 & YCrCb 4:4:4 ,Other Feature Support Flags : No_sRGB, Preferred Timing Mode, No_Display is continuous frequency (Multi-mode Base EDID and Extension Block))	0A	00001010
Panel Color Coordinates	25	19	Red/Green Low Bits (RxRy/GxGy)	25	00100101
	26	1A	Blue/White Low Bits (BxBy/WxWy)	D5	10010101
	27	1B	Red X Rx = 0.629	A1	10100001
	28	1C	Red Y Ry = 0.350	59	01011001
	29	1D	Green X Gx = 0.349	59	01011001
	30	1E	Green Y Gy = 0.614	9D	10011101
	31	1F	Blue X Bx = 0.154	27	00100111
	32	20	Blue Y By = 0.112	1C	00011100
	33	21	White X Wx = 0.313	50	01010000
	34	22	White Y Wy = 0.329	54	01010100
Established Timing	35	23	Established timing 1 (Optional_00h if not used)	00	00000000
	36	24	Established timing 2 (Optional_00h if not used)	00	00000000
	37	25	Manufacturer's timings (Optional_00h if not used)	00	00000000
Standard Timing ID	38	26	Standard timing ID 1 (Optional_01h if not used)	01	00000001
	39	27	Standard timing ID 1 (Optional_01h if not used)	01	00000001
	40	28	Standard timing ID 2 (Optional_01h if not used)	01	00000001
	41	29	Standard timing ID 2 (Optional_01h if not used)	01	00000001
	42	2A	Standard timing ID 3 (Optional_01h if not used)	01	00000001
	43	2B	Standard timing ID 3 (Optional_01h if not used)	01	00000001
	44	2C	Standard timing ID 4 (Optional_01h if not used)	01	00000001
	45	2D	Standard timing ID 4 (Optional_01h if not used)	01	00000001
	46	2E	Standard timing ID 5 (Optional_01h if not used)	01	00000001
	47	2F	Standard timing ID 5 (Optional_01h if not used)	01	00000001
	48	30	Standard timing ID 6 (Optional_01h if not used)	01	00000001
	49	31	Standard timing ID 6 (Optional_01h if not used)	01	00000001
	50	32	Standard timing ID 7 (Optional_01h if not used)	01	00000001
	51	33	Standard timing ID 7 (Optional_01h if not used)	01	00000001
	52	34	Standard timing ID 8 (Optional_01h if not used)	01	00000001
	53	35	Standard timing ID 8 (Optional_01h if not used)	01	00000001

LG Display

LP156WF4
Liquid Crystal Display

Product Specification

APPENDIX A. Enhanced Extended Display Identification Data (EEDID™)　2/3

Byte (Dec)	Byte (Hex)	Field Name and Comments		Value (Hex)	Value (Bin)
54	36	Pixel Clock/10,000 (LSB)	138 MHz @ 60 Hz	E8	11101000
55	37	Pixel Clock/10,000 (MSB)		35	00110101
56	38	Horizontal Active (HA)　(lower 8 bits)	1920 pixels	80	10000000
57	39	Horizontal Blanking (HB)　(lower 8 bits)	168 pixels	A8	10101000
58	3A	Horizontal Active (HA) / Horizontal Blanking (HB) (upper 4:4bits)		70	01110000
59	3B	Vertical Avtive (VA)	1080 line	38	00111000
60	3C	Vertical Blanking (VB) (DE Blanking typ for DE only panels)	22 lines	16	00010110
61	3D	Vertical Active (VA) / Vertical Blanking (VB)　(upper 4:4bits)		40	01000000
62	3E	Horizontal Front Porch in pixels (HF)　(lower 8 bits)	32 pixels	20	00100000
63	3F	Horizontal Sync Pulse Width in pixels　(HS)　(lower 8 bits)	36 pixels	24	00100100
64	40	Vertical Front Porch in lines (VF) : Vertical Sync Phuse Width in lines (VS)　(lower 4 bits)　5 lines : 5 lines		55	01010101
65	41	Horizontal Front Porch/ Sync Pulse Width/ Vertical Front Porch/ Sync Pulse Width (upper 2bits)		00	00000000
66	42	Horizontal Vedio Image Size (mm) (lower 8 bits)	345 mm	59	01011001
67	43	Vertical Vedio Image Size　(mm) (lower 8 bits)	194 mm	C2	11000010
68	44	Horizontal Image Size / Vertical Image Size　(upper 4 bits)		10	00010000
69	45	Horizontal Border = 0 (Zero for Notebook LCD)		00	00000000
70	46	Vertical Border = 0　(Zero for Notebook LCD)		00	00000000
71	47	Non-Interlace, Normal display, no stereo, Digital Separate [Vsync_NEG, Hsync_NEG (outside of V-sync)]		18	00011000
72	48	Flag		00	00000000
73	49	Flag		00	00000000
74	4A	Flag		00	00000000
75	4B	Data Type Tag　(Descriptor Defined by manufacturer)		00	00000000
76	4C	Flag		00	00000000
77	4D	Descriptor Defined by manufacturer		00	00000000
78	4E	Descriptor Defined by manufacturer		00	00000000
79	4F	Descriptor Defined by manufacturer		00	00000000
80	50	Descriptor Defined by manufacturer		00	00000000
81	51	Descriptor Defined by manufacturer		00	00000000
82	52	Descriptor Defined by manufacturer		00	00000000
83	53	Descriptor Defined by manufacturer		00	00000000
84	54	Descriptor Defined by manufacturer		00	00000000
85	55	Descriptor Defined by manufacturer		00	00000000
86	56	Descriptor Defined by manufacturer		00	00000000
87	57	Descriptor Defined by manufacturer		00	00000000
88	58	Descriptor Defined by manufacturer		00	00000000
89	59	Descriptor Defined by manufacturer		00	00000000
90	5A	Flag		00	00000000
91	5B	Flag		00	00000000
92	5C	Flag		00	00000000
93	5D	Data Type Tag (Alphanumeric Data String (ASCII String))		FE	11111110
94	5E	Flag		00	00000000
95	5F	Alphanumeric Data String (ASCII String)	L	4C	01001100
96	60	Alphanumeric Data String (ASCII String)	G	47	01000111
97	61	Alphanumeric Data String (ASCII String)		20	00100000
98	62	Alphanumeric Data String (ASCII String)	D	44	01000100
99	63	Alphanumeric Data String (ASCII String)	i	69	01101001
100	64	Alphanumeric Data String (ASCII String)	s	73	01110011
101	65	Alphanumeric Data String (ASCII String)	p	70	01110000
102	66	Alphanumeric Data String (ASCII String)	l	6C	01101100
103	67	Alphanumeric Data String (ASCII String)	a	61	01100001
104	68	Alphanumeric Data String (ASCII String)	y	79	01111001
105	69	Manufacturer P/N(If<13 char--> 0Ah, then terminate with ASC Ⅱ code 0Ah,set remaining char = 20h)		0A	00001010
106	6A	Manufacturer P/N(If<13 char--> 0Ah, then terminate with ASC Ⅱ code 0Ah,set remaining char = 20h)		20	00100000
107	6B	Manufacturer P/N(If<13 char--> 0Ah, then terminate with ASC Ⅱ code 0Ah,set remaining char = 20h)		20	00100000

Timing Descriptor #1 (bytes 54–71), *Timing Descriptor #2* (bytes 72–89), *Timing Descriptor #3* (bytes 90–107)

LG Display

LP156WF4
Liquid Crystal Display

Product Specification

APPENDIX A. Enhanced Extended Display Identification Data (EEDID™)   3/3

	Byte (Dec)	Byte (Hex)	Field Name and Comments		Value (Hex)	Value (Bin)
Timing Descriptor #4	108	6C	Flag		00	00000000
	109	6D	Flag		00	00000000
	110	6E	Flag		00	00000000
	111	6F	Data Type Tag (Alphanumeric Data String (ASCII String))		FE	11111110
	112	70	Flag		00	00000000
	113	71	Alphanumeric Data String (ASCII String)	L	4C	01001100
	114	72	Alphanumeric Data String (ASCII String)	P	50	01010000
	115	73	Alphanumeric Data String (ASCII String)	1	31	00110001
	116	74	Alphanumeric Data String (ASCII String)	5	35	00110101
	117	75	Alphanumeric Data String (ASCII String)	6	36	00110110
	118	76	Alphanumeric Data String (ASCII String)	W	57	01010111
	119	77	Alphanumeric Data String (ASCII String)	F	46	01000110
	120	78	Alphanumeric Data String (ASCII String)	4	34	00110100
	121	79	Alphanumeric Data String (ASCII String)	-	2D	00101101
	122	7A	Alphanumeric Data String (ASCII String)	S	53	01010011
	123	7B	Alphanumeric Data String (ASCII String)	P	50	01010000
	124	7C	Alphanumeric Data String (ASCII String)	B	42	01000010
	125	7D	Alphanumeric Data String (ASCII String)	1	31	00110001
Chec	126	7E	Extension flag (# of optional 128 panel ID extension block to follow, Typ = 0)		00	00000000
	127	7F	Check Sum (The 1-byte sum of all 128 bytes in this panel ID block shall = 0)		69	01101001